

Changing from Tube-type to Tubeless



Old/Current Wheel			New Changeover		
Tube-Type Tire	Tube-Type Rim Design (Diameter X Width)	Conversion (Yes/No)	Replaced by Tubeless Tire	Preferred Tubeless Rim (D x W) inches	Tubeless Rim ID (Inches) Check Clearance
7.50-15	15 x 6.00		9.00-17.5	17.5 x 6.75	14.5"
8.25-15	15 x 6.50	Yes	9.00-17.5	17.5 x 6.75	14.5"
9.00-15	15 x 7.00	Yes	10.00-17.5	17.5 x 6.75	14.5"
10.00-15	15 x 7.50	Yes	11.00-17.5	17.5 x 8.25	14.5"
16" Tube-type Tire Contact Wheels Now for conversions options - No Dual Options Only Singles					
7.50-20	20 x 6.00	Yes	9.00-22.5	22.5 x 6.75	19.5"
8.25-20	20 x 6.50	Yes	9.00-22.5	22.5 x 6.75	19.5"
9.00-20	20 x 7.00	Yes	10.00-22.5	22.5 x 7.50	19.5"
10.00-20	20 x 7.50	Yes	11.00-22.5	22.5 x 8.25	19.5"
11.00-20	20 x 8.00	Yes	12.00-22.5	22.5 x 8.25	19.5"
12.00-20	20 x 8.50		12.00-22.5	22.5 x 8.25	19.5"
14.00-20	20 x 10.00	Call	385/65R 22.5 OR 425/65R 22.5	22.5 x 12.25 OR 22.5 x 13.00	19.5"
10.00-22	22 x 7.50	Yes	11.00-24.5	24.5 x 8.25	21.5"
11.00-22	22 x 8.00	Yes	12.00-24.5	24.5 x 8.25	21.5"
11.00-24	24 x 8.00	Call	11.00-24.5 OR 12.00-24.5	24.5 x 8.25	21.5"
12.00-24	24 x 8.50	Call	11.00-24.5 OR 12.00-24.6	24.5 x 8.25	21.5"
14.00-24	24 x 10.00	Call	11.00-24.5 OR 12.00-24.7	24.5 x 8.25	21.5"